

□□□□□ TV □□ □□□□ □□□, □□□□□ □□□ TV □□ □□□□

Multifunctional intelligent industrial control board

Amlogic S922X / S905D3 / T972







V-By-One; Direct 4K Dot Screen; Android 9.0 Or Above
www.sztomato.com

□□□	
□□ □□.	□□□ S922X
CPU	Amlogic S922X 64□□ □□ □□ ARM® Cortex™ A73 CPU □□ □□ ARM® Cortex™ A53 CPU
GPU	ARM Mali™-G52 MP4 GPU □□□□
ROM	2G□/4GB LPDDR4
□□ □□□	16G B/ 64GB eMMC
□□□□	□□□□□ 9.0
□□□&□□□ □□	
□□/□□ □□	<p>□□ □□□□ □□□ □ □□□□ □□□ Amlogic Video Engine(AVE)</p> <p>HW UHD 4K H.265 75fps 10□□ □□□ □□□ □ □□ □□ □□ 1080p H.265/H.264 60fps □□□</p> <p>□□ 4Kx2K@60fps1x1080P@60fps□ □□ □□□ □□□ □□</p> <p>□□ "□□" □□□ □□□ □□□ □□ □□□ □□□□□□.</p> <p>□□□/□□ □□□</p> <p>VP9 □□□□-2 □□ 4Kx2K@60fps</p> <p>H.265 HEVC MP-10@L5.1 □□ 4Kx2K@60fps</p> <p>AVS2-P2 □□□□ □□ 4Kx2K@60fps</p> <p>H.264 AVC HP@L5.1 □□ 4Kx2K@30fps</p> <p>H.264 MVC □□ 1080P@60fps</p> <p>MPEG-4 ASP@L5 □□ 1080P@60fps(ISO-14496)</p> <p>WMV/VC-1 SP/MP/AP □□ 1080P@60fps</p> <p>AVS-P16(AVS) /AVS-P2 JiZhun □□□ □□ 1080P@60fps</p> <p>MPEG-2 MP/HL □□ 1080P@60fps(ISO-13818)</p> <p>MPEG-1 MP/HL □□ 1080P@60fps(ISO-11172)</p> <p>RealVideo 8/9/10 □□ 1080P@60fps</p> <p>□□ □□ □□□□ □□ 1080P@60fps□□ H.265/H.264 □□□ □□□</p> <p>□□□ □□ □□□ □□□ □□ □□□ □□</p> <p>MJPEG □ JPEG □□□ □□ □□□ □□□(ISO/IEC-10918)</p> <p>JPEG □□□, □□ □□, □□ □ □□ □□ □□</p> <p>*.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm □ *.jpg □□ □□ □□</p> <p>Dolby Vision □□, HDR10, HDR10, HLG □ PRIME HDR □□ □□</p>
□□□/□□ □□□	<p>□□/□□ □□□□ □□□ □□ □□□□ JPEG □ H.265/H.264 □□□</p> <p>JPEG □□□ □□□ H.265/H.264 □□□ □□□(□□ □□ □□□□ □□ 1080P@60fps)</p>
□□□□ □□	<p>CEC, Dynamic HDR □ HDCP 2.2□ □□ □□□□□ PHY□ □□ □□□□ □□□ HDMI 2.1 □□□,</p> <p>4Kx2K@60 □□ □□□ □□ C VBS 480i/576i □□ □□ □□</p> <p>□□ □□ SD/HD/FHD □□□ □□ □□ □□: 480i/p, 576i/p, 720p, 1080i/p □ 4Kx2K 4□□ MIPI DSI □□ □□,</p> <p>□□ □ □□ □□□ □□ □□ 1920*1080 □□□</p> <p>MP3, AAC, WMA, RM, FLAC, Ogg□ □□□□ 7.1/5.1 □□□□□□ □□□□□ □□</p> <p>□□□ □□ □□□ □□□ SPDIF/IEC958 □□/□□ □□ PCM □□/□□ □□□ TDM/PCM/I2S □□ 3□</p> <p>TDM/PCM □□: □□ 84kHz x32□□ x 8□□ □□ 96kHz x 32□□ x 32□□ □□□ I2S □□ □□ 384kHz x 32□□x8□□</p> <p>□□□□□ □□□ CIC, LPF □ HPF□ □□ □□□ □□□ PDM □□ □□, □□ 8□□ DMIC □□ □□□ □□□□ □□□ DAC</p> <p>□□□□□□□□ □□ I2SPCM □□□□ □□ □□ □□□ □□□ □□ □□ □□</p>
□□□□ □□	HD MPEG1/2/4, H.265/HEVC, HD AVC/VC-1, RM/RMVB, Xvid/DivX3/4/5/6, RealVideo8/9/10
□□□□ □□	Avi/Rm/Rm vb/Ts/Vob/Mkv/Mov/ISO/wmv/asf/flv/dat/mpg/mpeg
□□□□ □□	MP3/WMA/AAC/WAV/OGG/DDP/TrueHD/HD/FLAC/APE
□□□□ □□	HD JPEG/BMP/GIF/PNG/TIFF
□□	
USB □□□	USB2.0, □□480Mbps/USB3.0, □□5.1Gbps
SIM	□□□□ SIM
HDMI	HDMI 2.2/1□□ Lvds/1□□ EDP
□	RJ45 □□□ □□□ □□ 100/1000M □□□ □□

WiFi/BT	AP63985(WiFi/BT) 2.4G/5.8G
4G	PCIe
TF	MicroSD(Up to 128G)
HDD	SATA Max2TB (Optional)
Power	12V DC/3AΦ5.5*Φ2.5mm

It supports 4K video playback, 3D playback, AI image processing, etc. It also supports Dolby Vision, HDR10, HLG, and PRIME HDR.

Amlogic S922X is a 12nm AI SoC. It features a Cortex-A73 CPU, Cortex-A53 CPU, Mali-G52 MP4 GPU, and a 4K UHD video processor. It supports various video formats including H.264, H.265, VP9, and AV1. It also has a rich set of I/O interfaces like HDMI, USB, BT, and WiFi.

Features:

- o Amlogic S922X SoC with ARM® Cortex™ A73 CPU and ARM® Cortex™ A53 CPU
- o ARM Mali-G52 MP4 GPU
- o HW UHD 4K@60fps 10-bit video playback and 4K@60fps H.265/H.264 encoding
- o Dolby Vision, HDR10, HLG, and PRIME HDR support
- o Cortex-M4 co-processor
- o DRM support with TrustZone
- o WiFi, BT, USB, SD, and other I/O interfaces
- o Various other features

Amlogic S922X is an Android-based SoC for OTT/IPTV STB. It features a Cortex-A73 CPU, Cortex-A53 CPU, Mali-G52 MP4 GPU, and a 4K UHD video processor. It supports various video formats including H.264, H.265, VP9, and AV1. It also has a rich set of I/O interfaces like HDMI, USB, BT, and WiFi.

It features a Cortex-A73 CPU, Cortex-A53 CPU, Mali-G52 MP4 GPU, and a 4K UHD video processor. It supports various video formats including H.264, H.265, VP9, and AV1. It also has a rich set of I/O interfaces like HDMI, USB, BT, and WiFi.

It features a Cortex-A73 CPU, Cortex-A53 CPU, Mali-G52 MP4 GPU, and a 4K UHD video processor. It supports various video formats including H.264, H.265, VP9, and AV1. It also has a rich set of I/O interfaces like HDMI, USB, BT, and WiFi.



