

# OEM Android OEM Android

OS	Amlogic S928X-J OEM Android
CPU	Amlogic S928X-J ARM Cortex-A76 ARM Cortex-A55
GPU	ARM Mali-G57 MC2 4K GUI OpenGL ES 3.2 Vulkan 1.2 OpenCL 2.0
NPU	3.2 TOPS
RAM	64 GB DDR4 LPDDR4/4X 8GB DDR4266
eMMC	eMMC 5.1 SLC NAND Amlogic AVE AV1 MP-10 @ L6.1 8Kp60 VP9 Profile-2 @ 6.1 8Kp60 H.265 HEVC MP-10 @ L6.1 8Kp60 AVS3 1 8Kp60 AVS2-P2 8Kp60 H.264 AVC HP @ L5.2 4Kp60
Video	MPEG-4 WMV/VC-1 AVS MPEG-2 MPEG-1 1080p60 MJPEG JPEG (ISO/IEC-10918) 4x 4Kp60 JPEG 4Kp60 H.265 4Kp60 H.264 4Kp60 8 Amlogic TruLife Dolby Vision HDR10 HDR10+ HLG HDR Vivid
AI	3.2 TOPS (NNA) (TPU) TensorFlow Caffe
Connectivity	HDMI 2.1a PHY CEC HDR HDCP 2.2/2.3 8Kp60 eARC VRR QMS QFT ALLM DSC SBTM MP3 AAC WMA RM FLAC Ogg Vorbis Opus SRS TruVolume Dolby Audio DTS 7.1/5.1 VAD
Audio	SPDIF 192kHz 16/24/32 3 TDM/PCM/I2S TDM/PCM 48kHz x 32bits x 32ch 192kHz x 16bits x 16ch I2S 384kHz x 32bits x 16ch PDM CIC LPF HPF 8 DMIC DAC
Network	10/100/1000 MAC
USB	1x USB XHCI OTG 2.0 2x USB 2.0 1x USB 3.0 (5 Gbps) PCIe 2.0

# S928X



\* Supported configuration: PCIe 2.0 port + USB 2.0 Host, or USB3.0 port without PCIe.



Amlogic  
S928X  
M5A348.03  
812302W01100

DDR0

DDR1

JSY-3  
94V0  
E343782  
2309

G6008CC

RJ45

HDMI

Audio

220  
16V



YB910\_428\_V1.0 23082  
JSY-3  
94V0  
E343782  
2309

DDR0

DDR1

VDD\_DDR

G5000CC  
94V0  
R145

HDMI

220  
16V  
Audio



Amlogic S928X-J SoC ARM Cortex-A76 ARM Cortex-A55 8K SoC  
AV1 H.265 VP9 AVS3 AVS2 8Kp60 4K GUI SR

Amlogic S928X-J S928X-J

S928X-J ARM Cortex-A53 CPU 4K S928X-J

S928X-J 60 4K HDR10 HLG

S928X-J Mali-G31 MP2 GPU OpenGL ES3.2 Vulkan 1.1 OpenCL 2.0

S928X-J Android TV 10 Google Assistant

S928X-J chJip Wi-Fi 5.0 HDMI USB

Amlogic S928X-J S928X-J

8K Amlogic S928X-J Wi-Fi HDR 8K USB 3.0 5.0

Amlogic S928X-J 8K WiFi 6E Android 8K WiFi 6E Android

OEM Android Android

OEM Android OEM Android

OEM Android OEM Android

OEM Android OEM Android

OEM OEM

OEM Android OEM Android

OEM Android OEM Android

OEM TV Box Android OEM Android