Android TV Box Gigabit Ethernet, Android Internet TV Box Supplier



| Specifications | | |
|------------------------|--|--|
| Model No. | Amlogic S922X | |
| CPU | Amlogic S922X 64-bit quad core ARM® Cortex™ A73 CPU and dual core ARM® Cortex™ A53 CPU | |
| GPU | ARM MaliTM-G52 MP4 GPU processor | |
| ROM | 2GB/4GB LPDDR4 | |
| Internal Storage | 16GB/64GB eMMC | |
| OS | Android 9.0 | |
| Video&Audio CODEC | | |
| Video/Picture CODEC | Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders HW UHD 4K H.265 75fps 10-bit video decoder & low latency 1080p H.265/H.264 60fps encoder Support multi-video decoder up to 4Kx2K@60fps+1x1080P@60fps Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding Video/Picture Decoding VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 AVC up to 1080P@60fps (ISO-14496) WMV/VC-1 SP/MP/AP up to 1080P@60fps (ISO-14496) WMV/VC-1 SP/MP/AP up to 1080P@60fps (ISO-13818) MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) MPEG-2 MP/HL up to 1080P@60fps (ISO-11172) RealVideo 8/9/10 up to 1080P@60fps H.265/H.264 video encoding up to 1080P@60fps with low latency Multiple language and multiple format sub-title video support MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918) Supports JPEG thumbnail, scaling, rotation and transition effects Supports **.mkv,*.mmv,*.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats Supports Dolby VisionOptional, HDR10, HDR10+, HLG and PRIME HDR processing | |
| Video/Picture Encoding | Independent JPEG and H.265/H.264 encoder with configurable performance/bit-rate JPEG image encoding H.265/H.264 video encoding up to 1080P@60fps with low latency | |
| Video Output | Built-in HDMI 2.1 transmitter including both controller and PHY with CEC, Dynamic HDR and HDCP 2.2, 4Kx2K@60 max resolution output CVBS 480i/576i standard definition output Supports all standard SD/HD/FHD video output formats: 480i/p, 576i/p, 720p, 1080i/p and 4Kx2K 4-lane MIPI DSI interface resolution up to 1920*1080 with rotation and panel calibration Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing Built-in serial digital audio SPDIF/IEC958 input/output and PCM input/output 3 built-in TDM/PCM/I2S ports with TDM/PCM mode up to 84kHz x32bits x 8ch or 96kHz x 32bits x 32ch and I2S mode up to 384kHz x 32bitsx8ch Digital microphone PDM voice input with programmable CIC, LPF & HPF, support up to 8 DMICs Built-in stereo audio DAC Supports concurrent dual audio stereo channel output with combination of analog+PCM or I2S+PCM | |
| Decoder Format | HD MPEG1/2/4, H.265/HEVC, HD AVC/VC-1, RM/RMVB, Xvid/DivX3/4/5/6, RealVideo8/9/10 | |
| Media Format | Avi/Rm/Rmvb/Ts/Vob/Mkv/Mov/ISO/wmv/asf/flv/dat/mpg/mpeg | |
| Music Format | MP3/WMA/AAC/WAV/OGG/DDP/TrueHD/HD/FLAC/APE | |
| Photo Format | HD JPEG/BMP/GIF/PNG/TIFF | |
| Port | | |
| USB host | USB2.0, Max480Mbps/USB3.0, Max5.1Gbps | |
| SIM | MICRO SIM | |
| HDMI | HDMI 2.2/1ch Lvds/1ch EDP | |

| LAN | RJ45 wire Ethernet connection 100/1000M Ethernet support |
|-----------------|--|
| WiFi/ Bluetooth | AP6398S(Wi-Fi+BT) 2.4G+5.8G |
| 4G | PCIE Port |
| TF | microSD(Max 128G) |
| HDD | Support SATA Max2TB(Not included) |
| Power | |
| Power Supply | 12V DC/3AΦ5.5*Φ2.5mm |

This product is the network Android system motherboard, which is suitable for intelligent display terminal equipment, industrial automation terminal, computer vision/algorithm, 3D experience, game/entertainment equipment, high-performance Face Recognition calculation/storage, AI intelligence with high performance requirements. It can be widely used as the high-end demand intelligent mainboard of finance, advertising, security, transportation, public transportation and other industries.

This product adopts the latest generation of 12 nm ultra-low power AI chip s922x of Amlogic. It is an advanced application processor, integrating a powerful CPU, GPU subsystem, secure 4K video codec engine and first-class HDR image processing. The CPU of S922x main system adopts large and small architecture, which integrates four core arm cortex-a73 CPU cluster and dual core cortex-a53 cluster with unified secondary cache to improve system performance. Each CPU core includes a separate neon SIMD coprocessor to improve the software media processing capacity. Ave-10 can decode 4kx2k resolution video at a speed of 75 frames/second, and has a complete trusted video path (TVP) for security applications, supporting complete formats, including: MVC, MPEG-1/2/4, vc-1/WMV, AVS, AVS +, avs2 realvideo, MJPEG stream, H.264, h265-10, VP9 and JPEG pictures without size restrictions. The independent encoder can encode JPEG or h.265/h.264 format, up to 1080p, 75 frames per second. It supports 4kx2k @ 60fp (3840 * 2160) output of hdmi2.2 interface and 4K point screen of V by one interface. It supports HDCP 2.2, stereo audio DAC, CVBS output, 4channel Mipi DSI interface, multi TDM, PCM, I2S and SPDIF digital audio I/O interface, 8-Channel far-field PDM digital microphone (dmic) input and DVP camera interface. The product comes with 2x2 WiFi (supporting 2.4G and 5.8G dual frequency) + 4.1 wireless network module, supporting Gigabit Ethernet interface and infrared remote control, keyboard and mouse operation.

Highlights

- o Amlogic 64-bit quad core ARM® Cortex™ A73 CPU and dual core ARM® Cortex™ A53 CPU
- o ARM Mali-G52 MP4 GPU processor
- o HW UHD 4KH.265 75fps 10-bit video decoder & low latency 1080p H.265/H.264 60fp sencoder
- o Dolby Visionand HDR10, HDR10+, HLG and PRIME HDR video processing
- o Build in Cortex-M4 core for always on processing
- TrustZone based security for DRM video streaming
- o WIFI, BT, USB, SD, Ethernet, Analog Audio
- o Power management auxiliary processor

Amlogic S922X is an advanced application processor designed for Android hybrid OTT/IPTV Set Top Box(STB) and high-end media box applications. It integrates a powerful CPU, GPU subsystem, a secured 4K video CODEC engine and a best-in-class HDR image processing pipeline withall major peripherals to form the ultimate high-performance multimedia AP.

The main system CPU is based on Big. Little architecture which integrates a quad-core ARM Cortex-A73 CPU cluster and a dual-core Cortex-A53 cluster with united L2 cache to improve systemper formance. Each CPU core includes the separate NEON SIMD co- processor toimprove software media processing capability.


The graphic subsystem consists of twographic engines and a flexible video/graphic output pipeline. The ARM Mali-G52 MP4 GPU handles all OpenGL ES 3.2 Vulkan 1.0 and OpenCL 2.0 graphic programs, while the 2.5D graphics processor handles additional scaling, alpha, rotation and color space conversion operations. Together, the CPU and GPU handle all operating system, networking, user-interface and gaming relatedtasks. The video output pipeline includes Dolby Visionoptional HDR10, HDR10+,HLG and PRIME HDR processing, REC709/BT2020 processing, motion adaptive edgee nhancing de-interlacing, flexible programmable scalar, and manypicture enhancement filters before passing the enhanced image to the video outputports.


Amlogic Video Engine (AVE-10) offloads the Cortex-A53 CPUs from all video CODEC processing. It includes dedicated hardwarevideo decoder and encoder. AVE-10 is capable of decoding 4Kx2K resolution videoat 75fps with complete Trusted Video Path (TVP) for secure applications and supports full formats including MVC, MPEG- 1/2/4, VC-1/WMV, AVS, AVS+, AVS2 RealVideo, MJPEG streams, H.264, H265-10, VP9 and also JPEG pictures with nosize limitation. The independent encoder is able to encode in JPEG orH.265/H.264 up to 1080p at 60fps.


Amlogic S922X integrates all standard audio/video input/output interfaces including a HDMI2.1 transmitter with 3D, Dynamic HDR, CEC and HDCP 2.2 support, stereo audio DAC, a CVBS output, 4-lane MIPI DSI interface, multiple TDM, PCM, I2S and SPDIF digital audio input/output interfaces, 8 channel far-field PDM digital microphone (DMIC) inputs and a DVPcamera interface.

Amlogic S922X also integrates a set offunctional blocks for digital TV broadcasting streams. The built-in two demuxcan process the TV streams from the serial and parallel transport stream input interface, which can connect to external tuner/demodulator.

The processor has rich advanced network and peripheral interfaces, including a 10/100/1000M Ethernet MAC with RGMII, 10/100M Ethernet PHY, one USB XHCI OTG 2.0 port, one USB 3.0 and PCIe







Unmatched Connectivity and Performance Our Android TV Box Gigabit Ethernet provides ultrafast internet speeds, ensuring smooth streaming, lag-free gaming, and seamless browsing. With Gigabit Ethernet connectivity, you can enjoy a stable and reliable internet connection for all your entertainment needs.

Seamless Streaming of 4K Content Experience stunning visuals and crisp clarity with our Android TV Box. Stream your favorite movies, TV shows, and videos in 4K resolution, delivering an immersive viewing experience like never before. Our device supports popular streaming platforms, ensuring access to a vast library of content.

Advanced Features for Enhanced User Experience Our Android TV Box comes equipped with advanced features such as voice control, remote management, and compatibility with various apps and services. With voice commands, you can easily search for content, adjust settings, and navigate through menus. Remote management allows you to control your device from your smartphone or tablet, adding convenience to your entertainment setup.

Reliable and Trustworthy Android Internet TV Box Supplier As a trusted Android Internet TV Box Supplier, we prioritize quality, performance, and customer satisfaction. Our devices undergo rigorous testing to ensure reliability and durability, providing you with a long-lasting entertainment solution. With our Android TV Box Gigabit Ethernet, you can enjoy a seamless and immersive entertainment experience in the comfort of your home.

Enhanced Connectivity Options In addition to Gigabit Ethernet, our Android TV Box offers multiple connectivity options, including Wi-Fi, Bluetooth, USB, HDMI, and more. Connect external devices such as keyboards, mice, game controllers, and storage drives to expand your entertainment possibilities.

Versatile Entertainment Solutions With our Android TV Box, you can access a wide range of entertainment options. Stream movies and TV shows, play games, listen to music, view photos, browse the web, and more, all from one convenient device. Our Android TV Box caters to diverse entertainment preferences, making it the ideal choice for every household.

Conclusion In conclusion, our <u>Android TV Box</u> Gigabit Ethernet delivers unmatched connectivity, seamless streaming, and advanced features for an exceptional entertainment experience. As a reliable Android Internet TV Box Supplier, we are committed to providing high-quality devices that meet the needs of our customers. Upgrade your home entertainment setup with our cutting-edge Android TV Box and enjoy a world of entertainment at your fingertips.