

Android TV Box 4K: Your Gateway to Enhanced Visuals and Immersive Sound

Specifications	
Model No.	Amlogic S922X Android TV Box 4K
CPU	Amlogic S922X Quad Core ARM Cortex A73 and Dual Core ARM Cortex A53 1.98Ghz
GPU	ARM Mali-G52 MP4 (6EE) OpenGL ES 3.2, Vulkan 1.1 and OpenCL 2.0
RAM	DDR4 2GB/4GB
ROM	16GB eMMC (Expandable up to 128GB)
OS	Android 9.0
Video&Audio CODEC	
Decoding resolution	Support 4K H265 10Bit, H.264, AVS, MPEG-2 and many other formats
Multimedia Support	Support MPEG1, MPEG2, MPEG4, H.264, WMV, MKV, TS, flv and other video formats; Support MP3 and other audio formats; support JPG, JPEG, BMP, PNG, GIF and other photo formats
Port	
Video output	1 channel LVDS 40-pin 2.0mm double-pin, can support 8bit, 10bit screen; 1 channel HDMI output; 1 channel AV output
Video input	x1, MIPI CSI
Audio output	4-pin 2.5mm socket 25W@2 amplifier and 3W@2 speaker
Network interface	x1, 10M/100M Ethernet WIFI+BT, 2.4G single band or 2.4G/5G dual band for options PCIE slot (4G) x1 or M.2 slot (4G) x1 for options
USB2.0 interface	USB OTG x1 (available for HOST) USB HOST x7
Backlight interface	x2, 6-pin 2.0mm socket
Infrared interface	x1, 7-pin 2.0mm socket, supports both red and green LED indicators
Function expansion port	Serial ports x4
TF card slot	x1
SIM card slot	x1
RTC	Supports time synchronization
Power	
Power Supply	12V, 2.5DC Connector

This product is the network Android system motherboard, which is suitable for intelligent display terminal equipment, industrial automation terminal, computer vision/algorithm, 3D experience, game/entertainment equipment, high-performance Face Recognition calculation/storage, AI intelligence with high performance requirements. It can be widely used as the high-end demand intelligent mainboard of finance, advertising, security, transportation, public transportation and other industries.

This product adopts the latest generation of 12 nm ultra-low power AI chip s922x of Amlogic. It is an advanced application processor, integrating a powerful CPU, GPU subsystem, secure 4K video codec engine and first-class HDR image processing. The CPU of S922x main system adopts large and small architecture, which integrates four core arm cortex-a73 CPU cluster and dual core cortex-a53 cluster with unified secondary cache to improve system performance. Each CPU core includes a separate neon SIMD coprocessor to improve the software media processing capacity. Ave-10 can decode 4kx2k resolution video at a speed of 75 frames/second, and has a complete trusted video path (TVP) for security applications, supporting complete formats, including: MVC, MPEG-1/2/4, vc-1/WMV, AVS, AVS +, avs2 realvideo, MJPEG stream, H.264, h265-10, VP9 and JPEG pictures without size restrictions. The independent encoder can encode JPEG or h.265/h.264 format, up to 1080p, 75 frames per second. It supports 4kx2k @ 60fp (3840 * 2160) output of hdmi2.2 interface and 4K point screen of V by one interface. It supports HDCP 2.2, stereo audio DAC, CVBS output, 4-channel Mipi DSI interface, multi TDM, PCM, I2S and SPDIF digital audio I/O interface, 8-Channel

far-field PDM digital microphone (dmic) input and DVP camera interface. The product comes with 2x2 WiFi (supporting 2.4G and 5.8G dual frequency) + 4.1 wireless network module, supporting Gigabit Ethernet interface and infrared remote control, keyboard and mouse operation.

Highlights

- o Amlogic 64-bit quad core ARM® Cortex™ A73 CPU and dual core ARM® Cortex™ A53 CPU
- o ARM Mali-G52 MP4 GPU processor
- o HW UHD 4K@60fps 10-bit video decoder & low latency 1080p H.265/H.264 60fps encoder
- o Dolby Vision and HDR10, HDR10+, HLG and PRIME HDR video processing
- o Build in Cortex-M4 core for always on processing
- o TrustZone based security for DRM video streaming
- o WIFI, BT, USB, SD, Ethernet, Analog Audio
- o Power management auxiliary processor

Amlogic S922X is an advanced application processor designed for Android hybrid OTT/IPTV Set Top Box (STB) and high-end media box applications. It integrates a powerful CPU, GPU subsystem, a secured 4K video CODEC engine and a best-in-class HDR image processing pipeline with all major peripherals to form the ultimate high-performance multimedia AP.

The main system CPU is based on Big. Little architecture which integrates a quad-core ARM Cortex-A73 CPU cluster and a dual-core Cortex-A53 cluster with united L2 cache to improve system performance. Each CPU core includes the separate NEON SIMD co-processor to improve software media processing capability.


The graphic subsystem consists of two graphic engines and a flexible video/graphic output pipeline. The ARM Mali-G52 MP4 GPU handles all OpenGL ES 3.2 Vulkan 1.0 and OpenCL 2.0 graphic programs, while the 2.5D graphics processor handles additional scaling, alpha, rotation and color space conversion operations. Together, the CPU and GPU handle all operating system, networking, user-interface and gaming related tasks. The video output pipeline includes Dolby Vision optional HDR10, HDR10+, HLG and PRIME HDR processing, REC709/BT2020 processing, motion adaptive edge enhancing de-interlacing, flexible programmable scalar, and many picture enhancement filters before passing the enhanced image to the video output ports.

Amlogic Video Engine (AVE-10) offloads the Cortex-A53 CPUs from all video CODEC processing. It includes dedicated hardware video decoder and encoder. AVE-10 is capable of decoding 4Kx2K resolution video at 75fps with complete Trusted Video Path (TVP) for secure applications and supports full formats including MVC, MPEG-1/2/4, VC-1/WMV, AVS, AVS+, AVS2 RealVideo, MJPEG streams, H.264, H.265-10, VP9 and also JPEG pictures with no size limitation. The independent encoder is able to encode in JPEG or H.265/H.264 up to 1080p at 60fps.

Amlogic S922X integrates all standard audio/video input/output interfaces including a HDMI 2.1 transmitter with 3D, Dynamic HDR, CEC and HDCP 2.2 support, stereo audio DAC, a CVBS output, 4-lane MIPI DSI interface, multiple TDM, PCM, I2S and SPDIF digital audio input/output interfaces, 8 channel far-field PDM digital microphone (DMIC) inputs and a DVP camera interface.

Amlogic S922X also integrates a set of functional blocks for digital TV broadcasting streams. The built-in two demux can process the TV streams from the serial and parallel transport stream input interface, which can connect to external tuner/demodulator.

The processor has rich advanced network and peripheral interfaces, including a 10/100/1000M Ethernet MAC with RGMII, 10/100M Ethernet PHY, one USB XHCI OTG 2.0 port, one USB3.0 and PCIe






180mm

95mm

180mm*95mm*20mm



Board Introduction

Amlogic S922X Android Development Board multimedia network player-LCD driver integrated board adopts Amlogic S922X 12nm high-end chip, which supports UHD 4K@60fps hardware video decoding. It also supports supports H.265 10-bit, H.264 and AVS+ and many other formats. Support HDR10 and HLG high dynamic range processing, with multi-channel UART and USB interfaces. Support Bluetooth, WIFI, 4G and Ethernet functions. Support AV serial use, SD card expansion. Perfectly supports all kinds of touch screens, suitable for high-performance intelligent display terminal equipment, industrial automation terminal, computer vision/algorithm, 3D experience, game/amusement equipment, high-performance face recognition computing/storage, AI intelligence, etc. It can be widely used as a high-end intelligent motherboard for various industries such as finance, advertising, security, transportation, and public transportation.

(1) With various interfaces

- 1 channel LVDS video output (40pins)
- 1 channel HDMI video output
- 5 channels USB2.0
- 4 channels RS232 (can be modified to USB2.0 by patch)
- 1 channel MIPI CSI
- 1 channel AV output

- 1 channel I2C
- I2SC/IS2B
- 1 channel 25W super power amplifier and 3W speaker interface
- (2) Hybrid networking to break through network constraints
- Support wired, WiFi and 4G access, can realize multi-network hybrid networking
- (3) Easy to operate & fast maintenance
- Support breakpoint playback
- Super multi-period timing switch function
- Support U disk loading or direct playback
- Support automatic repair, remote upgrade, intelligent domain name resolution

Chip Performance

CPU Sub-system

- (1) Quad Core ARM Cortex-A73 and Dual Core ARM Cortex-A53 CPU
- (2) ARMv8-A architecture with Neon and Crypto extensions
- (3) Unified system L2 cache
- (4) Build-in Cortex-M4 core for always on processing
- (5) Advanced TrustZone security system
- (6) Application based traffic optimization using internal QoS-based switching fabrics

3D Graphics Processing Unit

- (1) ARM Mali-G52 MP4 (4ppc) GPU
- (2) 8-wide warps, 2x dual texture pipe, 6x8-wide execution engines(EE)
- (3) Concurrent multi-core processing
- (4) OpenGL ES3.2, Vulkan 1.0 and OpenCL 2.0 support

Video/Picture CODEC

- (1) Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders
- (2) Support multi-video decoder up to 4Kx2K@60fps+1x1080P@60fps
- (3) Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding
- (4) Video/Picture Decoding
 - VP9 Profile-2 up to 4Kx2K@60fps
 - H.265 HEVCMP-10@L5.1 up to 4Kx2K@60fps
 - AVS2-P2 Profile up to 4Kx2K@60fps
 - H.264 AVCHP@L5.1 up to 4Kx2K@30fps
 - H.264 MVC up to 1080P@60fps
 - MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)
 - WMV/VC-1 SP/MP/AP up to 1080P@60fps
 - AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps
 - MPEG-2 MP/HL up to 1080P@60fps(ISO-13818)
 - MPEG-1MP/HL up to 1080P@60fps(ISO-11172)
 - RealVideo 8/9/10 up to 1080P@60fps
- Multiple language and multiple format sub-title videosupport
- MJPEG and JPEG unlimited pixel resolution decoding(ISO/IEC-10918)
- Supports JPEG thumbnail, scaling, rotation and transition effects
- Supports *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats
- (5) Video/Picture Encoding
 - Independent JPEG and H.265/H.264 encoder with configurable performance/bit-rate
 - JPEG image encoding
 - H.265/H.264 video encoding up to 1080P@60fps with low latency

Video Output

- (1) Built-in HDMI 2.1 transmitter including both controller and PHY with CEC, Dynamic HDR and HDCP 2.2, 4Kx2K@60 max resolution output
- (2) CVBS 480i/576i standard definition output

- (3) Supports all standard SD/HD/FHD video output formats: 480i/p, 576i/p, 720p, 1080i/p and 4Kx2K
- (4) 4-lane MIPI DSI interface, resolution up to 1920*1080 with rotation and panel calibration

Chip Performance

CPU Sub-system

- (7) Quad Core ARM Cortex-A73 and Dual Core ARM Cortex-A53 CPU
- (8) ARMv8-A architecture with Neon and Crypto extensions
- (9) Unified system L2 cache
- (10) Build-in Cortex-M4 core for always on processing
- (11) Advanced TrustZone security system
- (12) Application based traffic optimization using internal QoS-based switching fabrics

3D Graphics Processing Unit

- (5) ARM Mali-G52 MP4 (4ppc) GPU
- (6) 8-wide warps, 2x dual texture pipe, 6x8-wide execution engines (EE)
- (7) Concurrent multi-core processing
- (8) OpenGL ES3.2, Vulkan 1.0 and OpenCL 2.0 support

Video/Picture CODEC

- (6) Amlogic Video Engine (AVE) with dedicated hardware decoders and encoders
- (7) Support multi-video decoder up to 4Kx2K@60fps+1x1080P@60fps
- (8) Supports multiple "secured" video decoding sessions and simultaneous decoding and encoding
- (9) Video/Picture Decoding

VP9 Profile-2 up to 4Kx2K@60fps

- H.265 HEVCMP-10@L5.1 up to 4Kx2K@60fps
- AVS2-P2 Profile up to 4Kx2K@60fps
- H.264 AVCHP@L5.1 up to 4Kx2K@30fps
- H.264 MVC up to 1080P@60fps
- MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)
- WMV/VC-1 SP/MP/AP up to 1080P@60fps
- AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps
- MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)
- MPEG-1MP/HL up to 1080P@60fps (ISO-11172)
- RealVideo 8/9/10 up to 1080P@60fps
- Multiple language and multiple format sub-title video support
- MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918)
- Supports JPEG thumbnail, scaling, rotation and transition effects
- Supports *.mkv, *.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats

(10) Video/Picture Encoding

- Independent JPEG and H.265/H.264 encoder with configurable performance/bit-rate
- JPEG image encoding
- H.265/H.264 video encoding up to 1080P@60fps with low latency

Video Output

- (5) Built-in HDMI 2.1 transmitter including both controller and PHY with CEC, Dynamic HDR and HDCP 2.2, 4Kx2K@60 max resolution output
- (6) CVBS 480i/576i standard definition output
- (7) Supports all standard SD/HD/FHD video output formats: 480i/p, 576i/p, 720p, 1080i/p and 4Kx2K
- (8) 4-lane MIPI DSI interface, resolution up to 1920*1080 with rotation and panel calibration

With support for Ultra HD 4K resolution, it delivers stunning visuals that bring your favorite movies, TV shows, and games to life. The Amlogic S922X Octa-Core processor ensures smooth and lag-free performance, whether you're streaming, gaming, or multitasking.

This Android TV Box is equipped with multiple connectivity options, including Wi-Fi, HDMI, USB, and more, making it easy

to connect to your preferred devices and services. It runs on the Android platform, giving you access to a vast library of apps and content.

Its sleek and compact design seamlessly blends with your home entertainment setup. Elevate your TV experience with this device and unlock the world of Android TV, offering a wealth of streaming, gaming, and productivity options.

Upgrade your home entertainment setup with the Amlogic S922X Octa-Core Ultra HD 4K Android [TV Box](#) and redefine how you experience entertainment. Explore the limitless possibilities of Android TV now!

Experience entertainment like never before with our Android TV Box 4K. Immerse yourself in stunning visuals and captivating sound quality, bringing your favorite movies, shows, and games to life in breathtaking detail.

Discover the ultimate entertainment experience with our Android TV Box 4K. Here's why it's the perfect addition to your home entertainment setup:

1. **Crystal-Clear 4K Resolution:** Enjoy breathtaking clarity and lifelike detail with support for 4K resolution, ensuring every scene comes to life with vivid colors and sharp contrast.
2. **Immersive Surround Sound:** Transform your living room into a cinematic experience with immersive surround sound capabilities, delivering rich, dynamic audio that pulls you into the heart of the action.
3. **Seamless Streaming:** Stream your favorite content from popular apps like Netflix, YouTube, and more with ease, thanks to the seamless integration of Android TV platform, ensuring endless entertainment options at your fingertips.
4. **Powerful Performance:** Equipped with advanced hardware and processors, our Android TV Box delivers smooth and responsive performance, allowing you to multitask effortlessly and navigate through menus with ease.
5. **Versatile Connectivity:** Connect your TV Box to various devices and peripherals with multiple connectivity options including HDMI, USB, and Bluetooth, expanding your entertainment possibilities even further.

Unlock a world of entertainment possibilities with our [Android TV Box](#) 4K. Elevate your viewing experience and enjoy endless hours of entertainment with unparalleled visual quality and immersive sound.